



NOTES:

1. IT IS CRITICAL SIPS ARE SEALED FOLLOWING DETAILS TO PREVENT POTENTIAL MOISTURE DAMAGE.
2. MAKE CERTAIN SURFACES ARE CLEAN, DRY, AND FREE OF DIRT AND FOREIGN MATERIALS PRIOR TO PLACEMENT OF SEALANT.
3. ALWAYS APPLY 3/8" DIAMETER CONTINUOUS BEAD.
4. ALWAYS APPLY SEALANT IN A STRAIGHT LINE.
5. STORE SEALANT IN A WARM AREA PRIOR TO INSTALLATION DURING COLD WEATHER.
6. FAILURE TO FOLLOW SEALANT APPLICATION DETAILS WILL VOID WARRANTY.
7. REFER TO SEALANT SAFETY DATA SHEETS.
8. AFTER PRODUCTION DETAILS ARE GENERATED WE WILL INCLUDE ENOUGH SEALANT TO APPLY (2) 3/8" BEADS AROUND THE ENTIRE FABRICATED PANEL PERIMETER INCLUDING OPENINGS. WE THEN ADD 20% EXTRA AS A BUFFER. IF YOU REQUIRE ADJUSTMENT TO THE SEALANT PROVIDED BE SURE TO NOTIFY PREMIER PRIOR TO SIGNING A CONTRACT OF SALE.

FULL 3/8" ϕ BEAD SEALANT IS REQUIRED. NOT A FLATTENED 3/8" WIDE RIBBON. SEALANT WILL SPREAD DURING ASSEMBLY.

